

HEXA FOR™ 6282

SHORT PERFLUORINATED CHAIN SURFACE PROTECTION AGENT

DESCRIPTION

HEXA FOR™ 6282 is a solvent-based pure methacrylic fluorinated polymer with high Flash Point based only on **C6 fluorinated chains** that supplies a durable and transparent surface treatment to building materials such as *Natural Stones, Terra Cotta, Concrete, Bricks*. It provides excellent water and oil repellency, stain resistance against *olive and seeds oil, coffee, ketchup, mustard...* The treated surfaces are easy cleanable. HEXA FOR™ 6282 does not change the original appearance of the stone.

SPECIAL FEATURES

- ❖ Excellent water and oil repellency
- ❖ Anti stain properties
- ❖ Easy to clean properties
- ❖ Durable treatment
- ❖ High penetration
- ❖ UV resistance
- ❖ High Flash Point
- ❖ Meets the goals of the voluntary U.S. EPA 2010/2015 PFOA Stewardship Program
- ❖ Targeted below LOD for PFOA (**PFOA free***)

APPLICATIONS

HEXA FOR™ 6282 expresses its best properties diluted to 5 – 10% in most common solvents (see SOLUBILITY). It can be applied with low-pressure deck sprayer, saturated brush, roller or by mop application in one or two layers of 100 – 150 g/m² of the diluted solution depending on the porosity of surface to be treated.

TECHNICAL INFORMATIONS

APPEARANCE	Pale yellow, clear liquid
ODOUR	Characteristic
DENSITY	0,92 g/cm ³
FLASH POINT	> 70°C (> 158°F)
BOILING POINT	> 190°C (> 374°F)
FREEZING POINT	< -20°C (< -4°F)
ACTIVE MATTER	24 - 26 % (wt)
COMPOSITION	25 % Fluorinated polymer 25 % DPM 50 % Distillates (petroleum), light fraction 'hydrotreating'

TECHNICAL SPECIFICATION

Solid content: 24 – 26%

STORAGE AND STABILITY

HEXA FOR™ 6282 is stable for one year and more if stored in original closed drums.

PERSONAL SAFETY

HEXA FOR™ 6282 does not contain toxic substances. Consult the current Material Data Sheet for safety use of the product.

Maflon S.p.A.

Via Don Ravizza snc
24060 Castelli Calepio (BG) IT
Phone +39.035.4494311
Accounting Dept. Fax +39.035.4425249

VAT N. IT 04080020169
REA N. 433424
Cap. Sociale € 100.000 interamente versato

Fluorochemical Specialties
<http://www.maflon.com> - info@maflon.com
Technical Dept. Fax +39.035.4494331



UNI EN ISO 9001:2008





TECHNICAL DATA SHEET



SOLUBILITY

Hydrocarbons, Ester, Ketones, Heptane, Toluene, Xylene, Dipropylenglycol monomethylether, 2-Propanol and Isoparaffins previous dilution in DPM.

PACKAGING

- ❖ Kg 25 – Drum
- ❖ Kg 100 – Drum
- ❖ Kg 180 – Drum

* Wherever the term "PFOA Free" is used in this website, it means content of PFOA is less than limit of detection (20ppb).

Maflon S.p.A.

Via Don Ravizza snc
24060 Castelli Calepio (BG) IT
Phone +39.035.4494311
Accounting Dept. Fax +39.035.4425249

VAT N. IT 04080020169
REA N. 433424
Cap. Sociale € 100.000 interamente versato

Fluorochemical Specialties
<http://www.maflon.com> - info@maflon.com
Technical Dept. Fax +39.035.4494331



UNI EN ISO 9001:2008



December 2015. The Information contained in this form and any verbal information are provided to the best of our knowledge. Not assume responsibility for incorrect or outdated information, except for agreements reached or otherwise for any contractual obligations. These information are outdated in the face of publishing a new edition.